

TECHNICAL DATA SHEET

AIRPRO SECURE PLUS BASEBALL BUMP CAP

DESCRIPTION

AirPro SecurePlus has been designed to provide unrivaled head retention and wearer comfort with the introduction of our innovative, first-to-market, Ratchet headband.

SPECIFICATION

| Product Codes and Cap Options | Code | Peak Type | Weight |
|-------------------------------|--------------------------------|--------------|--------|
| | S38KR | Standard | 153g |
| | S38KRPR | Reduced Peak | 148g |
| | S38NBR | Standard | 153g |
| | S38NBRPR | Reduced Peak | 148g |
| Size | 54 - 62cm | | |
| Peak | Standard (50mm) Reduced (30mm) | | |

MATERIALS


| | |
|-------------------|--|
| Shell | ABS (Acrylonitrile-Butadiene-Styrene) |
| Cap Cover | Polyester with DuPont Teflon® wipe clean and water resistant coating |
| Pads | Crown pad – Polyethylene Side pads – Polyethylene Ratchet pad - Ultra-sonically welded Polyester |
| Internal headband | Polyester |
| Ratchet | Polycarbonate, Polyamide, Acetal and Polypropylene components |

COLOURS


| | Navy Blue | Black |
|-------------|-----------|-------|
| Colour Code | NB | K |
| RAL | 5013 | 9017 |
| Pantone | 533 | 426 |

Please note: the closest matching RAL colours are listed.

CORPORATE BADGING



| Front | |
|-------|-------|
| ↔ | 100mm |
| ↕ | 65mm |



| Sides (transfer printing only) | |
|--------------------------------|------------|
| ↔↕ | 100 x 25mm |
| ↔↕ | 40 x 50mm |



EUROPEAN STANDARDS WITH OPTIONS

| Product | EN 812:2012 | | | Options outside the scope of EN 812 | Meets specification requirements of EN ISO 20471:2013 +A1 :2016 (High visibility warning clothing) | ISO 14116:2008 Index 3 | ISO 11611:2007 Para 6.7 | ISO 11612:2008: Para 6.3 after wash and dry cycles (ISO 15797:2002 procedure 8) | GO/RT 3279 Railway Group Standard for High Visibility Clothing |
|----------------------|-------------------------|---------------------|-----------------------------------|-------------------------------------|--|------------------------|-------------------------|---|--|
| | -30°C (Low Temperature) | F (Flame Resistant) | 440V a.c. (Electrical Resistance) | -40°C (Low Temperature) | | | | | |
| Standard Peak S38*R | ✓ | | | ✓ | | | | | |
| Reduced Peak S38*RPR | ✓ | | | ✓ | | | | | |

ACCESSORIES

| | |
|-------------|---|
| Ventilation | Via mesh crown panels above perforated shell and pad, breathable Polyester cap fabric and perforated side pads; all designed to provide optimum ventilation |
| Adjustment | Wheel Ratchet |

PACKAGING AND MAINTENANCE

| | |
|-----------|--|
| Packaging | 20 per colour, box size 46 x 28.5 x 33.5cm, box weight 3.5kg |
| Storage | Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C) May be stored in the dark for up to 5 years Do not store in direct/high heat or sunlight as this may distort the shell |
| Lifetime | The Centurion cap has an in-use life of up to 5 years Excessive wear and tear can considerably reduce the lifespan of the product |
| Cleaning | Cap Cover: Hand Wash Only. Do not Bleach, Iron, Tumble Dry or Dry Clean. Can be wiped clean to remove general spills and dirt due to it's protective DuPont Teflon coating. Cap Shell and Central Pad: Separate, rinse under a tap, dry and refit into the cap cover. |